



DisplayPort™ 1.1 Cable with Latches

- Certified to DisplayPort 1.1 standards
- High bandwidth, pure digital audio/video signals from your PC to your display.
- Quality-made from 28 AWG copper wire
- Fully shielded to protect against EMI/RFI
- Nickel-plated connectors
- Lifetime warranty.

Specifications: DisplayPort™ 1.1 Cable with Latches

Video characteristics:

Compliance:	DisplayPort Specification v1.1a 1.62/2.7 Gbps data rate
Content protection:	HDCP™ 1.3 for DisplayPort and HDMI
Resolution support:	1080p @ 60 Hz (10/12-bit deep color up to 2.25Gbps)

Physical Specifications:

Voltage Rating:	30V
Operating Temperature:	-40°C to +70°C

Conductor 1 (5 pairs):

Conductor type:	28AWG (7/0.127) Tinned copper
Insulation:	Foamed PE + SKIN O.D. - 0.97 ± 0.05mm White/Brown, White/Red, White/Green, White/Blue White/Black
Drain wire:	30AWG (7/0.10) Tinned Copper
Foil shield:	Aluminium 100% coverage

DisplayPort Connector:

Connector Type:	20pin Male with latches
Contacts:	Gold plated
Shell:	Nickel plated
Insulation:	Black PBT
Dimensions (L x W):	48.4 x 20.0mm

Conductor 2 (4 conductors):

Conductor type:	28AWG (7/0.127) Tinned copper
Insulation:	HD-PE O.D. - 0.75 ± 0.05mm Red, Orange, Yellow, White

Overall cable:

Foil shield:	Aluminium 100% coverage
Braided shield:	24 x 9/0.008 Tinned copper 85% coverage
Jacket:	PVC - Black O.D. - 7.30 ± 0.15mm

Part Number	Description	Weight (kg)
81278	1m DisplayPort™ 1.1 Cable with Latches	0.10
81279	2m DisplayPort™ 1.1 Cable with Latches	0.18
84202	3m DisplayPort™ 1.1 Cable with Latches	0.25
81298	5m DisplayPort™ 1.1 Cable with Latches	0.41
84203	7m DisplayPort™ 1.1 Cable with Latches	0.55
84204	10m DisplayPort™ 1.1 Cable with Latches	0.79

