



## Economy SVGA Monitor and Y-Splitter Cables

- 28AWG Construction
- Foil Shielded
- Fully Molded Connectors

### Specifications: Economy SVGA Monitor and Y-Splitter Cables

#### Electrical Characteristics:

Conductor Resistance:	261.33Ω/km at 20°C max.
Insulation Resistance:	10MΩ/km at 20°C max. DC 500V
Dielectric Strength:	AC 500V/1 minute no breakdown

#### Physical Characteristics:

Voltage Rating:	30V	Approvals:	RoHS Compliant
Temperature Rating:	60°C	Warranty:	Lifetime
Minimum Bend Radius:	55.00 ± 1.50mm	Package Type:	Polybag

#### Conductor (Qty. 14):

Conductor Type:	28AWG (7/0.12) Tinned Copper
Insulation:	80°C PVC Low Toxic O.D. 0.80 ± 0.05mm

#### Overall Cable:

Shield:	Aluminium Foil 125% coverage min.
Drain Wire:	26AWG (7/0.16) Tinned Copper
Jacket:	PVC Low Toxic O.D. 5.50 ± 0.15mm

#### Connectors:

Connector Type:	HD15 - Male HD15 - Female
Contact Material:	Brass, Gold Flash
Insulation:	Black PBT
Dimensions (HxWxD):	17.0 x 33.0 x 56.0mm

\*Note: 9<sup>th</sup> Pin is unloaded.

	Male to Male	Male Female	Y-Cable
20cm	---	---	81173
2m	81161	81167	---
3m	81162	81168	---
5m	81163	81169	---

