



USB To Fast Ethernet Adapter

- IEEE 802.3u 100 BASE-T, TX compatible
- Supports full duplex or half duplex mode
- Supports suspended mode and remote wakeup
- Compliant with the standard specification of USB 1.1 and 2.0

Specifications: USB To Fast Ethernet Adapter

Cable Specifications:

Conductor (Qty. 1 Twisted Pair):

Conductor Type: 28AWG (7/0.12)
Tinned Copper
Insulation: HD-PE
O.D. 0.85 ± 0.05mm
Colours: (white, green)

Conductor (Qty. 2):

Conductor Type: 28AWG (7/0.12)
Tinned Copper
Insulation: SR-PVC
O.D. 0.85 ± 0.05mm
Colours: black, red

Overall Cable:

Foil Shield: Aluminium Mylar
100% Coverage
Braided Shield: 16/4/0.10
Tinned Copper
65% Coverage
Jacket: PVC
Translucent White
O.D. 3.8 ± 0.10mm

Connector Specifications:

USB Connector:

Connector Type: USB A Male
Contact Material: Brass
3µm Gold Plating
Insulation: White PBT

Ethernet Connector:

Connector Type: RJ45 (8P8C)
Contact Material: Brass
3µm Gold Plating
Insulation: Black PBT

Physical Characteristics:

Cable Length: 0.25m
USB Connector: USB Type A Male
Ethernet Connector: RJ45 (8P8C) Female
Ethernet Case Dimensions: 70.0 x 25.4 x 16.3mm
Weight: 0.101kg

Item Number	Description	Weight (kg)
81672	USB to Fast Ethernet Adapter	0.101

