



## Bulk Cat5E Cable

- Meets or exceeds Cat5E specifications
- 4-pair unshielded twisted pair (UTP) cable
- 24AWG solid bare copper conductor
- High density polyethylene insulation, PVC jacket
- Verified compliant with EIA/TIA standards by ETL
- Available in various colours
- Lifetime Warranty

# Specifications: Cat5E Moulded Snagless Patch Cable

## Electrical Characteristics:

Conductor DC Resistance:	89Ω/km (maximum)
Insulation Resistance:	100Ω/km (maximum)
Dielectric Strength:	500MV/m

## Physical Characteristics:

Wiring Scheme:	T568B
Approvals:	RoHS Compliant
Warranty:	Lifetime
Package Type:	Polybag

### Conductor (Qty. 4 twisted pair):

Conductor Type:	24AWG Solid Bare Copper
Insulation:	H-D PE
Diameter:	0.95 ± 0.02mm
Colours:	Blue, Blue-White, Orange, Orange-White, Green, Green-White, Brown, Brown-White

### Overall Cable:

Jacket:	FR-PVC or LSZH
Minimum Average Thickness:	0.55mm
Outer Diameter:	5.30 ± 0.15mm

Description	Length	Gray	Blue	White	Red	Orange
Cat5E UTP 350MHz Bulk Solid Conductor CMR-Rated Cable	305m	88000	88001	88002	88003	---
Cat5E Low Smoke Zero Halogen (LSZH) Bulk Solid Conductor Cable	305m	88004	88005	88006	88007	88008

