



Bulk Cat6 Cable

- Verified compliant with EIA/TIA Cat6 specifications by ETL
- 4-pair unshielded twisted pair (UTP) cable
- 24AWG solid bare copper conductor for superior conductivity
- Durable, high density polyethylene insulation, PVC jacket
- Polyethylene separator for enhanced NEXT, ELFEXT and RL bandwidth
- Available in various colours
- Lifetime Warranty

Specifications: Bulk Cat6 Cable

Electrical Characteristics:

Conductor DC Resistance:	9.38Ω/100m (maximum)
Impedance:	100Ω
Capacitance:	5600pf/100m
Propagation Delay:	545ns/100m (maximum)
Delay Skew:	45ns/100m (maximum)

Physical Characteristics:

Wiring Scheme:	T568B
Temperature Rating:	60°C
Voltage Rating:	30V
Approvals:	RoHS Compliant
Warranty:	Lifetime
Package Type:	Polybag

Conductor (Qty. 4 twisted pair):

Conductor Type:	24AWG Solid Bare Copper
Insulation:	H-D PE
Diameter:	0.98 ± 0.05mm
Colours:	Blue, Blue-White, Orange, Orange-White, Green, Green-White, Brown, Brown-White

Overall Cable:

Jacket:	PVC - CMG Rated
Minimum Average Thickness:	0.60mm
Outer Diameter:	6.20 ± 0.30mm

Description	Length	Gray	Blue
Cat6 UTP 350 MHz Solid PVC CMG-Rated Cable	305m	88034	88035
Cat6 UTP 350 MHz Solid PVC CMG-Rated Cable	305m	88066	88067

