



TruLink[®] HDMI[®] Over Cat5E Extender

- Extend your HDMI signal up to 60 metres
- Supports a Maximum resolution of 1920 x 1080
- Adjustable equalization to compensate for varying lengths of Cat5E cable
- Video Bandwidth: 2.25Gbps

Specifications: TruLink® HDMI® Over Cat5E Extender

Electrical Specifications:

Video Bandwidth:	2.25Gbps
Input TMDS Signal:	1.2V (Peak-to-Peak)
Input DDC Signal:	5V (Peak-to-Peak)
Resolution/Distance Supported:	40m 1920 x 1080 (1080p 12bit)
	60m 1920 x 1080 (1080i)
	60m 1280 x 720 (720p)

Power Adapter* Specifications:

Power Input:	100 - 240V~47/63Hz, 0.48A
Power Output:	5V, 2.5A
Pin Diameter	5.5mm
Center Pin Polarity:	Positive

*The power adapter must be connected to the DC input on the remote unit

Physical Characteristics:

Video Input Connector (Base):	HDMI Type A Female - 19pin
Video Output Connector (Remote):	HDMI Type A Female - 19pin
Connector Plating:	Gold, 15µm
Housing Material:	Metal
Operating Temperature Range:	0° - 70°C
Storage Temperature Range:	0° - 70°C
Weight:	0.827kg
Dimensions:	Base Unit: 7.00 x 2.55 x 7.00cm Remote Unit: 7.00 x 2.55 x 7.00cm

Item Number	Description	Weight (kg)
89027	TruLink HDMI over Cat5E Extender	0.827

