



## 3x5 Component Video and Audio Matrix Selector Switch

- High quality audio and video output to as many as five A/V devices such as TV displays, A/V receivers or other A/V devices
- High quality video input support from up to three standard or high-definition sources
- Digital multi-channel support for up to three TOSLINK audio sources
- Standard left/right RCA stereo audio support for two-speaker systems
- Front panel push-buttons source selection with tri-colour LED for quick input/output identification
- Slim line remote control
- Optional RS232 PC interface control for use with an automated remote control system

# Specifications: 3x5 Component Video and Audio Matrix Selector Switch

## Audio/Video Specifications:

---

Video Bandwidth:	-3dB at 300MHz
Video Input Impedance:	75Ω
Optical Audio Output Level:	6μW
Audio Input Impedance:	10kΩ
Audio Input Level:	3V p-p
Signal to Noise Ratio:	65dB
Sampling Frequency:	44.1KHz

## Power Adapter Specifications:

---

Power Input:	100~240V/50~60Hz
Power Output:	12V, 500mA
Pin Diameter:	5.5mm
Center Pin Polarity:	Positive
Power Consumption:	6W

## Physical Characteristics:

---

Audio/Video Input Ports:	3 - Component Video RCA 3 - Digital Optical Audio 2 - Dual RCA Stereo Audio 1 - 3.5mm Stereo Audio
Audio/Video Output Ports:	5 - Component Video RCA 5 - Digital Optical Audio 5 - Dual RCA Stereo Audio
Control Options:	Front Panel Pushbuttons IR Remote Control Serial RS-232
Housing Material:	Metal
Weight:	2.972kg
Dimensions:	6.98 x 34.50 x 17.14cm

Item Number	Description	Weight (kg)
89028	3x5 Component Video and Audio Matrix Selector Switch	2.972

